
The Scientific Data Exchange Introductory Guide

<http://www.aps.anl.gov/DataExchange>

Version 0.0.13

May 3, 2012

Table 1: Version history

Version Date		Notes
0.9.0	May 3, 2012	saunders: Document ready for final review prior to version 1.0.0

Contents

1	Introduction	1
2	The Design of Data Exchange	2
2.1	HDF5	3
2.2	Data types	3
2.3	Root Level Structure	3
3	Data Exchange by Example	5
3.1	Diagram color code	5
3.2	A minimal Data Exchange file for imaging	5
3.3	Storing and describing a multidimensional dataset	6
3.4	Storing projections, dark fields, and white fields	6
3.5	A typical Data Exchange file for tomography	7
3.5.1	Sample Temperature Scan	7
3.5.2	X-ray Energy Scan	10
3.5.3	Detector-sample Distance Scan	11
3.5.4	Series of Tomographic Measurements	11
4	Data Exchange Core Reference	13
4.1	Top level (root)	13
4.2	Exchange	14
4.2.1	Storing and describing a multidimensional dataset	14
4.3	Measurement	16
4.3.1	Sample	16
4.3.1.1	Geometry	18
4.3.1.1.1	Translation	18
4.3.1.1.2	Orientation	18
4.3.1.2	Experiment	19
4.3.1.3	Experimenter	20
4.3.2	Instrument	20
4.3.2.1	Source	21
4.3.2.2	Shutter	22
4.3.2.3	Attenuator	23
4.3.2.4	Monochromator	23
4.3.2.5	Detector	24
4.4	Provenance	26
4.4.1	Process	26

A Appendix	29
A.1 Default units for Data Exchange entries	29
A.1.1 Angles	29
A.1.2 Dates	29
A.2 Geometry	30
A.2.1 Coordinate System	30
A.2.2 The local coordinate system of objects	30

1 Introduction

This document is a guide to the basic design principles and core guidelines for the Data Exchange file format. Briefly, Data Exchange is a set of guidelines for storing scientific data and metadata in a Hierarchical Data Format 5 (HDF5) file (<http://www.hdfgroup.org/HDF5>). The design guidelines for Data Exchange provide a starting point to which one may add custom data and metadata to solve particular problems.

This reference guide describes the basic design principles, examples of their application, a core reference for guidelines common to most uses, and coding examples.

2 The Design of Data Exchange

For various reasons, many x-ray techniques developed at synchrotron facilities around the world are unable to directly compare results due to their inability to exchange data and software tools. The aim of Data Exchange is to define a simple file format offering few basic rules and allowing each community to extend and add technique specific components. The goal is to provide extensibility in defining data, meta data and provenance information in a simple way that can be easily adopted by various x-ray techniques.

The Data Exchange format is implemented using Hierarchical Data Format 5 (HDF5), which offers platform-independent binary data storage with optional compression, hierarchical data ordering, and self-describing tags so that one can examine a HDF5 file's contents with no knowledge of how the file writing program was coded.

The aim and the scope of Data Exchange is very similar to the Coherent X-ray Imaging Data Bank file format (CXI), so whenever possible we will use the same conventions, name tags, and reference system. This document is using a similar diagram definition set by Filipe R. N. C. Maia in "CXI file format" (<http://cxidb.org/cxi.html>), with a few minor modifications for Data Exchange definitions.

The core principle of Data Exchange is that it must be simple enough that it is not necessary to use a support library beyond core HDF5. The simplicity of Data Exchange makes it easy for anyone to either look at an example file using `h5dump` or `HDFView`, or to look at example code in language X, and then create their own read and write routines in language Y.

The simplest Data Exchange file provides information sufficient to share a multidimensional data array. In this simplest form, Data Exchange implements only one "exchange" group. The "exchange" definition is designed to allow for simple exchange of images, spectra, and other forms of beamline detector data with a minimum of fields. This definition is essentially a technique-agnostic format for exchanging data with others. Data Exchange is also designed to be extended to include technique-specific data and metadata. This is achieved by providing optional, but clearly defined, metadata components to the base definition.

2.1 HDF5

The HDF5 format is the basis of the Data Exchange format. Data Exchange, like CXI, is not a completely new file format, but simply a set of rules designed to create HDF5 files with a common structure to allow a uniform and consistent interpretation of such files.

HDF5 was chosen as the basis because it is a widely used high performance scientific data format which many programs can already, at least partially, read and write. It also brings with it the almost automatic fulfillment of the Data Exchange requirements, i.e. simplicity, flexibility and extensibility. HDF5 version 1.8 or higher is required as previous versions don't support all features required by Data Exchange.

2.2 Data types

Data Exchange uses the same CXI convention for data types as defined at <http://cxidb.org/cxi.html> using HDF5 native datatypes. The data should be saved in the same format as it was created/acquired. For example CCD images acquired as 16 bit integers should be saved using the `H5T_NATIVE_SHORT` HDF5 type. In this way all cross platform big-little endian issues reading and writing files are eliminated.

2.3 Root Level Structure

While HDF5 gives great flexibility in data storage, straightforward file readability and exchange requires adhering to an agreed-upon naming and organizational convention. To achieve this goal, Data Exchange adopts a layered approach by defining a set of *mandatory* and *optional* fields.

The general structure of a Data Exchange file is shown in table 2. The most basic file must have an "implements" string, and an "exchange" group at the root level/group of the HDF5 file. Optional "measurement" and "provenance" groups are also defined. Beyond this, additional groups may be added to meet individual needs, with guidelines suggesting the best structure.

implements

Mandatory scalar string dataset in the root of the HDF5 file whose value is a colon separated list that shows which components are present in the file. All components listed in the *implements* string are to be groups placed in the HDF5 file at the root level/group.

Table 2: Data Exchange Top Level Members

Member	Type	Example
<i>implements</i>	string dataset	"exchange:measurement:provenance"
<i>exchange</i>	group	
<i>measurement</i>	group	
<i>provenance</i>	group	

In a minimal Data Exchange file, the only mandatory item in this list is *exchange*. A more general Data Exchange file also contain *measurement* and possibly *provenance*, in which case the implements string would be: "*exchange: measurement: provenance*"

exchange

Mandatory group containing one or more arrays that represent the most basic version of the data, such as raw or normalized optical density maps or a elemental signal map. *Exchange_N* is used when more than one core dataset or derived datasets are saved in the file. The *exchange* implementation for specific techniques are defined in separate sections in the Reference Guide.

measurement

Optional group containing the measurement made on the sample. *Measurement* contains information about the sample and the instrument. *Measurement_N* is used when more than one measurement is stored in the same file.

provenance

Optional group containing information about the status of each processing step.

In a Data Exchange file, each dataset has a unit defined using the *units* attribute. *units* is not mandatory - if omitted, the default unit as defined in [Appendix A.1](#) is used.

The detailed rules about how to store datasets within the exchange group are best shown through examples in the next section. Detailed reference information can be found in the [Data Exchange Core Reference](#) section.

3 Data Exchange by Example

The examples in this section show how one can store data for imaging experiments using the Data Exchange format. It is general enough, however, to show how Data Exchange can be extended or adapted to other techniques. These examples are meant to give a flavor for our approach. A complete reference to the core structure can be found in Section 4. Technique specific extensions to the core structure can be found starting with Section ??

3.1 Diagram color code

All the diagrams in this section follow the color conventions shown in Figure 1. The basic elements are HDF5 datasets, attributes, and groups. We also support internal references to elements in the file by a simple scalar string that holds the path of the dataset within the file. On the diagram, this is shown as a reference dataset that points to the referred-to dataset. Note that we use this mechanism rather than HDF5 hard or soft links




Figure 1: Explanation of the color code used in the diagrams

3.2 A minimal Data Exchange file for imaging

Figure 2 shows a diagram of a minimal Data Exchange file to store a single projection image. As no units or axes are specified, the data is assumed to be in “counts” with the axes (x, y) in pixels.




Figure 2: Diagram of a minimal Data Exchange file for a single image.

3.3 Storing and describing a multidimensional dataset

A multidimensional dataset may be stored with no units or axes attributes. In this minimal case, the units are assumed to be "count". Any other interpretation necessarily involves an implicit agreement between the file writer and reader. If there is no axis attribute, each axis is simply a linear integer dimension scale typically interpreted as pixels.

To describe the dataset further and provide for automatic interpretation, a units attribute should be added. Data Exchange recommends using SI units as described in Appendix A.1. The description attribute may be used to characterize the dataset further. An axes attribute may be added containing colon separated names of additional datasets called dimension scales. For example, an axes attribute of "theta:y:x" combined with an additional one-dimensional dataset called theta containing the rotation angles of each projection, provides a complete description. Note that it is not necessary to include x and y datasets since those are assumed to be a linear integer scale (pixels). For other cases, it may be necessary to include a one-dim dataset to describe each axis.

3.4 Storing projections, dark fields, and white fields

A tomographic data set consists of a series of projections, dark and white field images. The dark and white fields must have the same projection image dimensions and can be collected at any time before, after or during the projection data collection. The angular position of the tomographic rotation axis, theta, can be used to keep track of when the dark and white images are collected. These examples show projection, dark, and white images saved in three 3D arrays as shown in Figure 3 and 4 using, by default, the natural HDF5 order of the a multidimensional array (rotation axis, ccd y, ccd x), i.e. with the fastest

changing dimension being the last dimension, and the slowest changing dimension being the first dimension. If using the default dimension order, the axes attribute "theta:y:x" can be omitted. The `axes` attribute is mandatory if the 3D arrays use a different axes order. This could be the case when, for example, the arrays are optimized for sinogram read (`axes = "y:theta:x"`). As no units are specified the data is assumed to be in "counts" with the axes (x, y) in pixels.

If the positions of the rotation axis for each projection, dark, and white images are not specified via theta dimension scale datasets, it is assumed that the raw projections are taken at equally spaced angular intervals between 0 and 180 degree, with white and dark field collected at the same time before or after the projection data collection.




Figure 3: Diagram of a minimal Data Exchange file for a single tomographic data set including raw projections, dark, and white fields.

3.5 A typical Data Exchange file for tomography

A series of tomographic data sets are typically collected changing the instrument status (energy, detector or optics position) or changing the sample status (position, environment etc.). Figure 5, 6 and 7 show the content of files changing the sample temperature, the x-ray source energy and detector-sample distance.

3.5.1 Sample Temperature Scan




Figure 4: Diagram of a minimal Data Exchange file for a single tomographic data set including raw projections, dark and white fields. In this case the attribute `axes` indicates the presence of theta vectors containing the positions of the rotation axis for each projection, dark and white images.




Figure 5: Diagram of two tomographic data sets taken at two different sample temperatures (100 and 200 K). To store the temperature in °C is necessary to add the attribute `units = "celsius"` to the `temperature` tag.

3.5.2 X-ray Energy Scan




Figure 6: Diagram of two tomographic data sets taken at two different energy (10 and 20 keV). To store the temperature in *keV* is necessary to add the attribute `units = "keV"` to the energy tag.

3.5.3 Detector-sample Distance Scan




Figure 7: Diagram of two tomographic data sets collected with two different detector-sample distances (5 and 9 mm). Note the use of `output_data` dataset to associate the detector with the exchange group generated from the acquisition.

3.5.4 Series of Tomographic Measurements

A series of tomographic measurements, when relevant, can be stored in the same file appending `_N` to the measurement tag. In nano tomography experiments, for example, the detector field of view is often smaller than the sample. To collect a complete tomographic data set, it is necessary to raster the sample across the field of view moving its x and y location. Figure 8 shows a file from a nano tomography experiment when the sample rasters through the field of view.




Figure 8: Diagram of a file with 4 tomographic data sets from a nano tomography experiment.

4 Data Exchange Core Reference

4.1 Top level (root)

This node represents the top level of the HDF5 file and holds some general information about the file.

Table 3: Top Level Members

Member	Type	Example
<i>implements</i>	string dataset	"exchange:measurement:provenance"
<i>exchange_N</i>	group	
<i>measurement_N</i>	group	
<i>provenance</i>	group	

implements

A colon separated list that shows which components are present in the file. The only *mandatory* component is *exchange*. A more general Data Exchange file also contains *measurement* and *provenance* information, if so these will be declared in *implements* as "exchange:measurement:provenance"

exchange_N

The data taken from measurements or processing.

measurement_N

Each measurement made on the sample.

provenance

The Provenance group describes all process steps that have been applied to the data.

4.2 Exchange

The exchange group is where scientific datasets reside. This group contains one or more array datasets containing n-dimensional data and optional descriptions of the axes (dimension scale datasets). Exactly how this group is used is dependent on the application, however the general idea is that one exchange group contains one cohesive dataset. If, for example, the dataset is processed into some other form, then another exchange group is used to store the derived data.

Multiple exchange groups are numbered consecutively as `exchange_N`. At a minimum, each exchange group should have a primary dataset named `data`. The title is optional.

Table 4: Exchange Group Members

Member	Type	Example
<code>title</code>	string dataset	"tomography projections"
<code>data</code>	array dataset	n-dimensional dataset

`title`

Descriptive title for data dataset.

data

The primary scientific dataset. Additional related datasets may have any arbitrary name. Each dataset may have description, units, and axes attributes.

Table 5: data attributes

Attribute	Type	Example
<code>description</code>	string attribute	"transmission"
<code>units</code>	string attribute	"counts"
<code>axes</code>	string attribute	"theta:y:x"

4.2.1 Storing and describing a multidimensional dataset

A multidimensional dataset may be stored with no units or axes attributes. In this minimal case, the units are assumed to be "count". Any other interpretation necessarily involves an implicit agreement between

the file writer and reader. If there is no axis attribute, each axis is simply a linear integer dimension scale typically interpreted as pixels.

To describe the dataset further and provide for automatic interpretation, a units attribute should be added. Data Exchange recommends using SI units as described in Appendix A.1. The description attribute may be used to characterize the dataset further. An axes attribute may be added containing colon separated names of additional datasets called dimension scales. For example, an axes attribute of "theta:y:x" combined with an additional one-dimensional dataset called theta containing the rotation angles of each projection, provides a complete description for tomography. Note that it is not necessary to include x and y datasets since those are assumed to be a linear integer scale (pixels). For other cases, it may be necessary to include a one-dim dataset to describe each axis.

4.3 Measurement

This group holds sample and instrument information.

Table 6: Measurement Group Members

Member	Type	Example
sample	group	
instrument	group	

sample

The sample measured.

instrument

The instrument used to collect this data.

4.3.1 Sample

This group holds basic information about the sample, its geometry, properties, the sample owner (user) and sample proposal information.

Table 7: Sample Group Members

Member	Type	Example
name	string dataset	"cells sample 1"
description	string dataset	"malaria cells"
preparation_date	string dataset (ISO 8601)	"2011-07-15T15:10Z"
chemical_formula	string dataset (abbr. CIF format)	"(Cd 2+)3, 2(H2 O)"
mass	float dataset	0.25
concentration	float dataset	0.4
environment	string dataset	"air"
temperature	float dataset	25.4
temperature_set	float dataset	26.0
pressure	float dataset	101325
thickness	float dataset	0.001
position	string dataset	"2D" APS robot coord.
geometry	group	
experiment	group	
experimenter	group	

name

Descriptive name of the sample.

description
 Description of the sample.

preparation_date
 Date and time the sample was prepared.

chemical_formula
 Sample chemical formula using the CIF format.

mass
 Mass of the sample.

concentration
 Mass/volume.

environment
 Sample environment.

temperature
 Sample temperature.

temperature_set
 Sample temperature set point.

pressure
 Sample pressure.

thickness
 Sample thickness.

position
 Sample position in the sample changer/robot.

geometry
 Sample center of mass position and orientation.

experiment
 Facility experiment identifiers.

experimenter
 Experimenter identifiers.

Table 8: Geometry Group Members

Member	Type	Example
translation	group	
orientation	group	

4.3.1.1 Geometry This class holds the general position and orientation of a component.

translation

The position of the object with respect to the origin.

orientation

The rotation of the object with respect to the coordinate system.

Only one orientation and one translation is permitted in each geometry class.

The position of the origin of the object should be explicitly defined for each object. If it is not defined it should be assumed to be the center of the object.

4.3.1.1.1 Translation This is the description for the general spatial location of a component - it is used by the Geometry class

Table 9: Translation Group Members

Member	Type	Example
distances	3 float array dataset	(0, 0.001, 0)

distances

The x, y and z components of the translation of the origin of the object relative to the origin of the global coordinate system (the place where the X-ray beam meets the sample when the sample is first aligned in the beam). If distances does not have the attribute units set then the units are in meters.

4.3.1.1.2 Orientation This is the description for a general orientation of a component - it is used by the Geometry class.

Table 10: Orientation Group Members

Member	Type	Example
value	6 float array dataset	

value

Dot products between the local and the global unit vectors. Unitless

The orientation information is stored as direction cosines. The direction cosines will be between the local coordinate directions and the global coordinate directions. The unit vectors in both the local and global coordinates are right-handed and orthonormal.

Calling the local unit vectors (x', y', z') and the reference unit vectors (x, y, z) the six numbers will be $[x' \cdot x, x' \cdot y, x' \cdot z, y' \cdot x, y' \cdot y, y' \cdot z]$ where “ \cdot ” is the scalar dot product (cosine of the angle between the unit vectors).

Notice that this corresponds to the first two rows of the rotation matrix that transforms from the global orientation to the local orientation. The third row can be recovered by using the fact that the basis vectors are orthonormal.

4.3.1.2 Experiment This provides references to facility ids for the proposal, scheduled activity, and safety form.

Table 11: Experiment Group Members

Member	Type	Example
proposal	string dataset	“1234”
activity	string dataset	“9876”
safety	string dataset	“9876”

proposal

Proposal reference number. For the APS this is the General User Proposal number.

activity

Proposal scheduler id. For the APS this is the beamline scheduler activity id.

safety

Safety reference document. For the APS this is the Experiment Safety Approval Form number.

4.3.1.3 Experimenter Description of a single experimenter. Multiple experimenters can be represented through numbered entries such as `experimenter_1`, `experimenter_2`.

Table 12: Experimenter Group Members

Member	Type	Example
name	string dataset	"John Doe"
role	string dataset	"Project PI"
affiliation	string dataset	"University of California, Berkeley"
address	string dataset	"EPS UC Berkeley CA 94720 4767 USA"
phone	string dataset	"+1 123 456 0000"
email	string dataset	"johndoe@berkeley.edu"
facility_user_id	string dataset	"a123456"

name **User name.**

role **User role.**

affiliation **User affiliation.**

address **User address.**

phone **User phone number.**

email **User e-mail address**

facility_user_id **User badge number**

4.3.2 Instrument

The instrument group stores all relevant beamline components status at the beginning of a measurement.

name

Name of the instrument.

source

The source used by the instrument.

Table 13: Instrument Group Members

Member	Type	Example
name	string dataset	"XSD/2-BM"
source	group	
shutter_ <i>N</i>	group	
attenuator_ <i>N</i>	group	
monochromator	group	
interferometer	group	
detector_ <i>N</i>	group	

shutter_*N*

The shutter(s) used by the instrument.

attenuator_*N*

The attenuators that are part of the instrument.

monochromator

The monochromator used by the instrument.

detector_*N*

The detectors that compose the instrument.

4.3.2.1 Source Class describing the light source being used.

Table 14: Source Group Members

Member	Type	Example
name	string dataset	"APS"
datetime	string dataset (ISO 8601)	"2011-07-15T15:10Z"
beamline	string dataset	"2-BM"
distance	float dataset	-48.5
current	float dataset	0.094
energy	float dataset	4.807e-15
pulse_energy	float dataset	1.602e-15
pulse_width	float dataset	15e-11
mode	string dataset	"TOPUP"
beam_intensity_incident	float dataset	55.93
beam_intensity_transmitted	float dataset	100.0

name

Name of the facility.

datetime

Date and time source was measured.

beamline

Name of the beamline.

distance

The source distance (m) from the sample.

current

Electron beam current (A).

energy

Characteristic photon energy of the source (J). For an APS bending magnet this is 30 keV or 4.807e-15 J.

pulse_energy

Sum of the energy of all the photons in the pulse (J).

pulse_width

Duration of the pulse (s).

source

Beam mode: TOPUP.

beam_intensity_incident

Incident beam intensity in (photons per s).

beam_intensity_transmitted

Transmitted beam intensity (photons per s).

4.3.2.2 Shutter Class describing the shutter being used.

Table 15: Shutter Group Members

Member	Type	Example
name	string dataset	"Front End Shutter 1"
distance	float dataset	-48.5
status	string dataset	"OPEN"

name

Shutter name.

distance

Shutter distance (m) from the sample.

status

"OPEN" or "CLOSED" or "NORMAL"

4.3.2.3 Attenuator This class describes the beamline attenuator(s) used during data collection. If more than one attenuators are used they will be named as attenuator_1, attenuator_2 etc.

Table 16: Attenuator Group Members

Member	Type	Example
distance	float dataset	-35.7
thickness	float dataset	1e-3
attenuator_transmission	float dataset	unit-less
type	string dataset	"Al"

distance

The Attenuator distance (m) from the sample. Negative distances represent beamline components that are before the sample while positive distances represent components that are after the sample. In this case the filter is located 35.7 m upstream of the sample.

thickness

Thickness of attenuator along beam direction.

attenuator_transmission

The nominal amount of the beam that gets through (transmitted intensity)/(incident intensity).

type

Type or composition of attenuator.

4.3.2.4 Monochromator Define the monochromator used in the instrument.

type

Multilayer type.

Table 17: Monochromator Group Members

Member	Type	Example
type	string dataset	"Multilayer"
energy	float dataset	1.602e-15
energy_error	float dataset	1.602e-17
mono_stripe	string dataset	"Ru/C"

energy

Peak of the spectrum that the monochromator selects. Since units is not defined this field is in J and corresponds to 10 keV.

energy_error

Standard deviation of the spectrum that the monochromator selects. Since units is not defined this field is in J.

mono_stripe

Type of multilayer coating or crystal.

4.3.2.5 Detector This class holds information about the detector used during the experiment. If more than one detector are used they will be all listed as detector_*N*.

Table 18: Detector Group Members

Member	Type	Example
manufacturer	string dataset	"Cooke Corporation"
model	string dataset	"pco dimax"
serial_number	string dataset	"1234XW2"
distance	float dataset	5e-3
output_data	string dataset	"/exchange"

manufacturer

The detector manufacturer.

model

The detector model.

serial_number

The detector serial number .

distance

Distance of the detector from the sample.

output_data

String HDF5 path to the exchange group where the detector output data is located.

4.4 Provenance

Data provenance is the documentation of all transformations, analyses and interpretations of data. Maintaining this history allows for reproducible data. The Data Exchange format permits tracking provenance using a combination of this Provenance group plus input/output datasets in the technique specific groups. Scientific users will not generally be expected to maintain data in this group. The expectation is that analysis pipeline tools will automatically record process steps using this group. In addition, it is possible to re-run an analysis using the information provided here.

The provenance group tracks the execution order of a series of processes using numbered process groups. Each process group uses references to other groups that describe the analysis in detail. Each process group represents the status of the process and some kind of informative summary message.

Table 19: Provenance Group Members

Member	Type	Example
<code>process_N</code>	group	

`process_N`

A process applied to the data.

4.4.1 Process

The process class holds basic information about a process. It is a generic container for recording the status of a process, and maintaining references to detailed, scientific domain-specific information.

Table 20: Process class members

Member	Type	Example
<code>status</code>	string dataset	"SUCCESS"
<code>actor</code>	string dataset	"reconstruction"
<code>reference</code>	string dataset	"/reconstruction"
<code>message</code>	string dataset	"Full reconstruction complete."

status

Current process status. May be one of the following: QUEUED, RUNNING, FAILED, or SUCCESS.

actor

Name of pipeline stage that executes this process group.

reference

Path to a process description group. The process description group contains all metadata to perform the specific process. This reference is simply the HDF5 path within this file of the technique specific process description group. The process description group should contain all parameters necessary to run the process, including the name and version of any external analysis tool used to process the data. It should also contain input and output references that point to the exchange_ *N* groups that contain the input and output datasets of the process.

message

A process specific message generated by the process. It may be a confirmation that the process was successful, or a detailed error message, for example.

Table 21: Provenance Group Example

process_1		
status		"SUCCESS"
reference		"/gridftp"
message		"detector controller to cluster data transfer"
process_2		
status		"SUCCESS"
reference		"/sinogram"
message		"modified axes from "theta:y:x" to "y:theta:x"
process_3		
status		"SUCCESS"
reference		"/ring_removal"
message		"ring removal algorithm complete"
process_4		
status		"SUCCESS"
reference		"/reconstruction"
message		"Full reconstruction complete."
process_5		
status		"RUNNING"
reference		"/export"
message		"converting reconstructed data to tiff"

A Appendix

A.1 Default units for Data Exchange entries

The default units for Data Exchange entries follow the CXI entries definition, i.e. are SI based units (see table 40) unless the "units" attribute is specified. Data Exchange prefers to use the default SI based units whenever possible.

Table 22: SI (and common derived) base units for different quantities

Quantity	Units	Abbreviation
length	meter	m
mass	kilogram	kg
time	second	s
electric current	ampere	A
temperature	kelvin	K
amount of substance	mole	mol
luminous intensity	candela	cd
frequency	hertz	Hz
force	newton	N
pressure	pascal	Pa
energy	joule	J
power	watt	W
electric potential	volt	V
capacitance	farad	F
electric resistance	ohm	Ω
absorbed dose	gray	Gy
area	square meter	m^2
volume	cubic meter	m^3

A.1.1 Exceptions

Angles are always defined in degrees *not* in radians and use the abbreviation "degree".

A.1.2 Times and Dates

Times and Dates are always specified according to the [ISO 8601](#). This means for example "1996-07-31T21:15:22+0600". Note the "T" separat-

ing the data from the time and the “+0600” timezone specification.

A.2 Geometry

A.2.1 Coordinate System

The Data Exchange uses the same CXI coordinate system. This is a right handed system with the z axis parallel to the X-ray beam, with the positive z direction pointing away from the light source, in the downstream direction. The y axis is vertical with the positive direction pointing up, while the x axis is horizontal completing the right handed system (see Fig. 9). The origin of the coordinate system is defined by the point where the X-ray beam meets the sample.




Figure 9: The coordinate system used by CXI. The intersection of the X-ray beam with the sample define the origin of the system. The z axis is parallel to the beam and points downstream.

A.2.2 The local coordinate system of objects

For many detectors their location and orientation is crucial to interpret results. Translations and rotations are used to define the absolute position of each object. But to be able to apply these transformations we need to know what is the origin of the local coordinate system of each object. Unless otherwise specified the origin should be assumed to be the geometrical center of the object in question. The default orientation of the object should have the longest axis of the object aligned with the x axis, the second longest with the y axis and the shortest with the z axis.